



Warning: On two wheel drive trucks a clearance check must be performed when truck is loaded and unloaded to verify the inverted ball will not interfere with the top of the differential.

### 600 Series Installation Kits (Rated to vehicles Max Gross Weight Rating)

Make/Model	Style	Years From	Years To	Double-Lock Hitch#	Quick Goose 2 Hitch#	Under-Bed Folding Ball Gooseneck Hitch #	Rail Kit#	Notes
<b>CHEVROLET/GMC</b>								
1500 & 2500LD Silverado/Sierra	New Body, 69.3", 78.7" & 97.6" Beds	2007	2012	60615	n/a	n/a	60632	Z
	Classic Body Only	1999	2007	60600	60630	61652	60652	Z
2500HD & 3500 Silverado/Sierra	Long & Short Beds	2011	2012	60607	n/a	n/a	60604	Z
	Classic & New Body	2001	2010	60600	60630	61652	60652	Z,4
2500 & 3500 Full Size Pickup Trucks	Old Body, Long & Short Beds	1999	2000	60600	60630	61652	60631	Z
	Not 34" Frame (O.D.)	1988	1998	60600	60630	61652	60631	Z
<b>DODGE</b>								
Ram 1500	All Beds, Including Mega & Crew Cab	2009	2012	60600	n/a	n/a	60657	Z
		2009	2010	60600	n/a	n/a	60656*	Z
		2002	2008	60600	60640	n/a	60659	Z,1,2
	All	1994	2001	60600	60640	n/a	60635	Z
Ram 2500 & 3500	All Beds, Including Mega Cab	2003	2012	60600	60640	n/a	60659	Z,1,2
	All	1994	2002	60600	60640	n/a	60635	Z
<b>FORD</b>								
F-150	All Beds	2004	2012	60600	60630	61652	60641	Z
		1997	2003	60600	60630	61652	60637	Z
		1980	1996	60600	60630	61652	60636	Z,1
	Heritage Edition Only	2004	2004	60600	60630	61652	60637	Z
F-250LD	All	1997	2003	60600	60630	61652	60637	Z
F-250 & F-350 Super Duty	Including Air Bag Overloads	2011	2012	60600	60630	61652	60644	Z,3
		1999	2010	60600	60640	n/a	60644	Z,3
		1999	2010	60600	60640	n/a	60643*	Z,3
F-250 & F-350	Without Overload Springs	1980	1998	60600	60630	61652	60636	Z
	With Overload Springs	1980	1998	60600	60630	61652	60636	Z
F-450 Super Duty	All, Except Cab & Chassis	2008	2012	60600	60640	n/a	60644	Z,3
		2008	2010	60600	60640	n/a	60643*	Z,3
<b>NISSAN</b>								
Titan	Long & Short Beds	2004	2012	60620	n/a	n/a	60664	Z,1
<b>TOYOTA</b>								
Tundra	6' 5" Bed Only	2007	2012	60600	n/a	n/a	60667	Z,5
	All Beds	2000	2006	60625	n/a	n/a	60665	Z,6

\*While Supplies Last

#### 600 Series Footnotes:

- 1 = Passenger side wheel well must be notched for frame rail access
- 2 = Parking brake cable bracket may require relocation
- 3 = Exhaust may have to be permanently lowered on 05 & newer models.
- 4 = Vacuum canister requires relocation (kit included)
- 5 = Ball cannot be turned over, brake lines must be cable tied (ties included)
- 6 = Do not invert ball with heavy loads on 2 wheel drive models
- Z = No frame drilling required

All Models: Brake, fuel, and electrical lines may need to be loosened or repositioned. Heat shield requires modification or removal

### 30 & 40 Series Installation Kits (30K Gross Towing Weight)

Make/Model	Style	Years From	Years To	New Double-Lock Hitch#	New Quick Goose2 Hitch#	New Rail Kit#	Notes
<b>CHEVROLET/GMC</b>							
1500, 1500HD, 2500LD, 2500HD Silverado/Sierra	Classic Body Only	1999	2007	63060	N/A	63234*	7
3500 Silverado	Classic Body Only	2001	2007	63060	N/A	63232*	7
2500 & 3500 Full Size Pickup Trucks	Old Body Style	1999	2000	63060	N/A	63231*	Z,8
	Not 34" Frame (O.D.)	1988	1998	63060	N/A	63231*	Z,8
<b>DODGE</b>							
Ram 1500	All	2002	2008	63060	N/A	63233*	9
		1994	2001	63060	N/A	63235*	Z
Ram 2500 & 3500	All, Including Mega Cab	2003	2008	63060	N/A	63245*	Z
		1994	2002	63060	N/A	63235*	Z
<b>FORD</b>							
F-150	All	2004	2008	63060	N/A	63241*	Z
		1997	2003	63060	N/A	63237*	9
		1980	1996	63060	N/A	63236*	Z
	Heritage Edition Only	2004	2004	63060	N/A	63237*	Z
F-250LD	All	1997	2003	63060	N/A	63237*	Z
F-250 & F-350 Super Duty	Includes Air Bag Overloads	1999	2008	63060	N/A	63242*	9
F-250 & F-350	Without Overload Springs	1980	1998	63060	N/A	63236*	Z
	With Overload Springs	1980	1998	63060	N/A	63236*	9
F-450	All, Except Cab & Chassis	2008	2008	63060	N/A	63242*	9

\*While Supplies Last

#### 30 & 40 Series Footnotes:

- 7 = Cut or remove heat shield, drill (2) 1/2" holes/side
- 8 = Relocate brake lines on driver side
- 9 = Remove heat shield, drill (2) 1/2" holes/side, tire removal
- Z = No frame drilling required

All Models: Brake, fuel, and electrical lines may need to be loosened or repositioned. Heat shield requires modification or removal